

NOTES:

- SUBMIT TYPE OF MIX AND INSTALLATION METHOD OF ASPHALT CONCRETE PAVING FOR APPROVAL PRIOR TO CONSTRUCTION.
- 2. CONTRACTOR IS RESPONSIBLE FOR COORDINATION OF SLEEVES, CONDUITS AND ANY OTHER UNDERGROUNDING PRIOR TO PLACEMENT OF AC PAVING SURFACE. COORDINATE WITH OTHER TRADES AS NECESSARY TO AVOID CONFLICT AND EXCAVATION INTO FINISHED SURFACES.
- 3. SEE PLANS FOR CONCRETE DEEP JOINTS, SCORE JOINTS, AND EXPANSION JOINTS. REFER TO PSD CONC-4 FOR DEEP JOINT DETAILING.
- 4. TENNIS COURT AND BASKETBALL COURT SURFACE COATINGS:
 - 4.1. <u>LEVELING SLURRY COURSE</u>: MATERIAL FOR LEVELING LOW AREAS AND FOR THE LEVELING COURSE SHALL BE ACRYLIC RESURFACER COATING MANUFACTURED BY "PLEXI-PAVE", OR AN APPROVED EQUAL MINERAL FILLED ACRYLIC EMULSION PRODUCT.
 - 4.2. <u>COLOR COATING</u>: COLOR COATING IS TO BE "PLEXI-PAVE" SYSTEM MANUFACTURED BY CALIFORNIA PRODUCTS CORP., OR APPROVED EQUAL. COLOR SHALL BE CHOSEN BY THE CITY. SUBMIT SAMPLES FOR CITY SELECTION PRIOR TO ORDERING MATERIAL.
 - 4.3. PAINT: PLEXICOLOR LINE PAINT BY CALIFORNIA PRODUCTS CORPORATION., OR APPROVED EQUAL.
 - 4.4. PROTECTIVE COATING: ON ALL SURFACES, APPLY TWO COATS OF "CLEAR-GLO 3", APPLIED OVER ALL COLOR COATINGS, MANUFACTURED BY CALIFORNIA PRODUCTS CORP., OR APPROVED EQUAL.

